

Element	Attribute	Function	Notes
<!-- ... -->	freely definable	documentation	Notes within a XML-file
<TxFrame ... > </TxFrame>		Start / End of a message	
ShowName	True False	Show the name of a message	Shows the name or the data of the message within the transmit list
Name	freely definable	Label of the message	
TransmitDelay	number	Delay before sending	In milliseconds (ms)
CycleTime	number	Time to repeat	In milliseconds (ms)
CycleCount	number	Number of transmission repetitions	"0" means send until aborted
<Message ... />		CAN telegram, message	
Identifier	Hex number 3 digits	CAN Identifier in CAN 2.0A	e.g. "0x300"
	Hex number 8 digits	CAN Identifier in CAN 2.0B	e.g. "0x00000108"
RTR	0 / 1	RTR Bit	Set Remote Request Bit
DLC	0 ... 8	Data Length Code	0 ... 8 Byte
D1 D2 ... D8	Hex number 2 digits	Databyte 1 Databyte 2 to 8	e.g. "0x01"
<Sequence ... > </Sequence>		Start / End of a sequence	Messages within these identifiers belong to the sequence
Name	freely definable	Label of the sequence	
CycleTime	number	Time to repeat	In Milliseconds (ms)
CycleCount	number	Number of transmission repetitions	"0" means send until aborted